



LED-1562HD

15" LED-backlit LCD monitor has optimal picture quality with native Full HD resolution (1920 x 1080). This latest generation model is ideal for any small screen, high quality video installations.

Benefits

- Displays native Full HD signals (1080i/p) with no downscaling
- LED backlight: brighter picture using less power
- Widescreen (16:9) native aspect ratio
- Multiple connections including HDMI, Composite and VGA
- Built-in removable desk stand
- Built-in speakers

Related Products

- LED-1562HDL: Flush-mount version of LED-1562HD
- LED-1562HDR: Rack-mount version of LED-1562HD
- LED-1562HDLX: Flush-mount version of LED-1562HD with no front controls

Specifications	
Mount	VESA 75 x 75mm; Removable Deskstand
HD Compatible	Yes
Anti Glare Coating	Yes
Case	Durable Metal
IR Remote Control	Yes
Native Aspect Ratio	16:9
Visible Screen Size (WH)	13.6" x 7.6" / 345 x 195mm
Resolution	1920(H) x 1080(V) (Full HD)
Brightness Rating	300 cd/m ² (Nit)
Contrast Ratio	600:1
Back Light	LED (30K)
PC Compatibility	Yes
Dot Pitch	0.17925(H) x 0.17925(V)mm
Color Depth	6-bit, 262K
Number of Pixels	2,073,600
Response Time	8ms (Rising/Falling)
Audio Power / Speakers	8 Ohm, 2 Speakers x 5 Watts
Viewing Angle (L/R/T/B)	70/70/60/60 degrees
Digital Signal Processor	3D Comb Filter
HDMI	x2 Inputs
Composite	x1 BNC Input; x1 BNC Output
VGA	x1 15-pin mini D-sub Input
RS-232	x1 Input
Audio	x1 RCA L/R Input; x1 3.5mm PC Input
Power	x1 2.1mm DC Input
Power Requirements	Regulated 12VDC; 3A; Negative Ground
Power Consumption	8 Watts (Max)
Operating Temp	32 ~ 104°F / 0 ~ 40°C
Humidity	10% ~ 90%
Dimensions w/ Deskstand	14.25" x 10.78" x 5.5"; 362 x 275 x 140mm
Dimensions	14.25" x 10.5" x 1.85"; 362 x 267 x 47mm
Weight	Net: 4.85 lbs / 2.2 kg

Specifications subject to change.