



## LED-1214HDT

This commercial-grade TV/monitor has a sleek design and durable housing which makes it ideal for nearly any retail, sports arena, hospitality and public-viewing application.

### Benefits

- LED backlight: brighter picture using less power
- HDMI Input provides unmatched picture sharpness and clarity
- ATSC/QAM digital TV tuner
- Built-in stereo speakers
- IR remote control
- USB Input provides easy accessibility for updates

### Accessories

- HM-401: Under-cabinet hinge mount
- WM-302: 4-way adjustable wall mount
- WM-31: Fixed wall mount bracket

### Related Products

- LED-1214HDTTC: Countertop mount TV monitor
- LED-1214HDTW: Wall mount TV monitor



Specifications	
Mount	VESA 75 x 75mm; Removable Deskstand
HD Compatible	Yes
Anti Glare Coating	Yes
Case	Durable ABS Plastic
IR Remote Control	Yes
Native Aspect Ratio	16:9
Visible Screen Size (WH)	10.3" x 6.4" / 261.1 x 163.2mm
Resolution	1280(H) x 800(V)
Brightness Rating	400 cd/m <sup>2</sup> (Nit)
Contrast Ratio	800:1
Back Light	LED (50K)
Dot Pitch	0.204(H) x 0.204(V) mm
Color Depth	16.7 million
Number of Pixels	1,024,000
Response Time	30ms (Rising/Falling)
Audio Power / Speakers	4 Ohm, 2 Speakers x 1 Watt
Viewing Angle (L/R/T/B)	80/80/65/80 degrees
Dimensions w/ Deskstand	12.6" x 9.5" x 2.1" / 320 x 240 x 52mm
Dimensions	12.6" x 9.5" x 1.5" / 320 x 240 x 36mm
Operating Temp	0° ~ 104°F / -17.8° ~ 40°C
Humidity	20% ~ 95%
Digital TV (ATSC/QAM) Tuner	x1 F Connector (Coax) Input
Power Requirements	Regulated 12VDC; 3Amps; Negative Ground
Power Consumption	30 Watts (Max)
HDMI	x1 Input
Component / Composite	x1 YPbPr Input; x1 RCA Input
VGA	x1 15-pin mini D-sub Input
USB	x1 Input
Audio	x1 RCA R/L Input; x1 3.5mm Input; x1 3.5mm Output
Power	x1 2.1mm DC Input
Weight	Net: 4.5 lbs / 2.1 kg; Gross: 7.25 lbs / 3.3 kg

Specifications subject to change.