



LED-1214HDTW

This commercial-grade, custom wall-mounted TV has a sleek design and durable housing which makes it ideal for nearly any retail, sports arena, hospitality and public-viewing applications.

Benefits

- ATSC/QAM TV tuner
- LED backlight: brighter picture using less power
- Custom wall-mount conceals signal and power cables
- Built-in stereo speakers
- IR remote control
- USB Input provides easy accessibility for updates

Related Products

- LED-1214HDT: 12" LCD TV monitor
- LED-1214HDT-C: Countertop mount TV monitor



Specifications	
Mount	Concealed cable wall-mount
HD Compatible	Yes
Anti Glare Coating	Yes
Case	Durable ABS Plastic
IR Remote Control	Yes
Native Aspect Ratio	16:9
Visible Screen Size (WH)	10.3" x 6.4" / 261.1 x 163.2mm
Resolution	1280(H) x 800(V)
Brightness Rating	400 cd/m ² (Nit)
Contrast Ratio	800:1
Back Light	LED (50K)
Dot Pitch	0.204(H) x 0.204(V)
Color Depth	16.7M
Number of Pixels	1,024,000
Response Time	30ms (Rising/Falling)
Audio Power / Speakers	4 Ohm, 2 Speakers x 1 Watt
Viewing Angle (L/R/T/B)	80/80/65/80 degrees
3D Comb Filter	Yes
Dimensions	12.6" x 9.5" x 1.5" / 320 x 240 x 36mm
Operating Temp	0° ~ 104°F / -17° ~ 40°C
Humidity	20% ~ 95%
Power Requirements	Regulated 12VDC; 3Amps; Negative Ground
Power Consumption	30 Watts (Max)
Digital TV (ATSC/QAM) Tuner	x1 F connector (coax) Input
HDMI	x1 Input
Component / Composite	x1 YPbPr Input; x1 RCA Input
PC	x1 15-pin mini D-sub Input
USB	x1 Input
Audio	x1 RCA R/L Input; x1 3.5mm Input; x1 3.5mm Output
Power	x1 2.1mm DC Input
Weight	Net: 4.5 lbs / 2.1 kg; Gross: 7.25 lbs / 3.3 kg

Specifications subject to change.