



## LED-566HDMI

This flush mount, LED-backlight monitor supports both analog and digital signals and can display up to high definition (1080i/p). It is primarily designed for in-wall video placements and used in a variety of transportation, security, and broadcast applications.

### Benefits

- LED backlight: brighter picture using less power
- Switchable 4:3 and 16:9 aspect ratios
- Multi-featured: Underscan, Blue Gun, RGB adjustable
- Monochrome and color peaking modes for fine control optimizing focus
- DSLR Scaling when connected to a still photography camera
- On-board memory retains last input source when power is off
- Sturdy metal housing
- Automatic scaling of signal resolution
- Excellent electromagnetic shielding
- Front controls allow the user to make adjustments via the On-Screen Display (OSD)

### Accessories

- DC-12: car cord

Specifications	
Mount	Flush Mount
Anti Glare Coating	Yes
Case	Durable Metal
Electromagnetic Shielding	Yes
Native Aspect Ratio	4:3
Visible Screen Size (WH)	4.4" x 3.3" / 112.9 x 84.7mm
Resolution	640 x 480 (displays 480i/p ~ 1080i/p)
Brightness Rating	350 cd/m <sup>2</sup> (Nit)
Contrast Ratio	500:1
Back Light	LED (20K)
Dot Pitch	0.0588mm x 0.1764mm
Color Depth	5600K ~ 6500K (User Adjustable)
Number of Pixels	307,200
Response Time	10/15ms (Rising/Falling)
Viewing Angle (L/R/T/B)	70/70/50/70 degrees
Dimensions	6.85" x 6.89" x 0.89" / 174 x 175 x 22.5mm
Operating Temp	-4 ~ 140°F / -20 ~ 60°C
Humidity	20% ~ 80%
Mirror Image	Yes
Signal Resolution Scaling	Automatic
NTSC/PAL Auto-sensing	Yes
Composite	x2 BNC Inputs
HDMI	x1 Input
Power	x1 2.1mm DC Input
Power Requirements	12VDC; 630mA
Power Consumption	5 Watts (Max)
Weight	Net: 0.88 lbs / 0.4 kg; Gross: 1.96 lbs / 0.88 kg

Specifications subject to change.