



LED-1004IP-PVM

This LED-backlit monitor includes a low profile, built-in IP camera for displaying and capturing activity in front of the monitor. This model is an ideal small screen theft deterrent device.

Benefits

- Built-in IP camera with auto and manual electronic shutter
- Camera captures and sends 720p high definition image
- 3D Comb Filter for better picture quality
- Secure access with password protection
- Aesthetically designed and durable metal case

Specifications	
Mount	VESA 75 x 75mm and 100 x 100mm; Removable Deskstand
HD Compatible	Yes
Anti Glare Coating	Yes; 3mm non-glare top glass is optional
Case	Durable Metal
IR Remote Control	Yes (Optional)
Native Aspect Ratio	4:3
Visible Screen Size (WH)	7.8" x 5.9" / 196.6 x 147.5mm
Resolution	1024(H) x 768(V)
Brightness Rating	350 cd/m ² (Nit)
Contrast Ratio	800:1
Dot Pitch	0.264(H) x 0.264(V)mm
Color Depth	262,144
Number of Pixels	786,432
Response Time	25ms (Rising/Falling)
Viewing Angle (L/R/T/B)	89/89/89/89 degrees
Digital Signal Processing	3D Comb Filter and 3D De-Interlace
Operating Temp	32 ~ 122°F / 0 ~ 50°C
Power Requirements	12VDC; 3A; Negative Ground
Power Consumption	36 Watts (Max)
Video Output (IP Camera)	x1 RJ45
Camera Image Sensor	1/4" 1.0 MP progressive CMOS
Camera Resolution	1280x720p@30fps
Frame Rate	720x480@30fps
Video Camera Compression	H.264 high profile; MPEG4; M-JPEG
Minimum Illumination	Color: 0.2Lux@F1.2; B/W: 0.05Lux@F1.2
Ethernet	10/100M Auto
Browser	IE 8.0 or higher
Alarm Trigger	File upload via FTP; notify via Email
Security Protection	ID/Password
Users	Supports 9 users
Power	x1 2.1mm DC Input
Weight	Net: 4.4 lbs / 2 kg; Gross: 7.5 lbs / 3.4 kg

Specifications subject to change.