



## LED-709HDM

This high-definition monitor with touch-screen capability is designed primarily for video production, remote surveillance, and mobile applications.

### Benefits

- LED backlight: brighter picture using less power
- Displays HD signals (1080i/p)
- 16:9 native aspect ratio
- Built-in 5-wire resistive touch screen when viewing a VGA source
- Battery pack option available for mobility

### Related Products

- LED-709HDM KIT: 7" LCD Monitor (metal case), battery pack, and totebag
- LED-709HD: 7" Field LCD Monitor (plastic case)
- LED-709HD KIT: 7" LCD Monitor (plastic case), battery pack, and totebag
- LED-709HDM-L: Flush-Mount 7" LCD Monitor
- LED-709HD2: Dual 7" LCD Monitors in a rack-mount

Specifications	
Mount	VESA 75 x 75mm
HD Compatible	Yes (displays 1080p)
Anti Glare Coating	Yes
Case	Durable Metal
IR Remote Control	No
Native Aspect Ratio	16:9
Visible Screen Size (WH)	6" x 3.4" / 154.08 x 85.92mm
Resolution	1024 x 600
Brightness Rating	250 cd/m <sup>2</sup> (Nit)
Contrast Ratio	700:1
Back Light	LED (20K)
Dot Pitch	0.0642(H) x 0.1790(V) mm
Number of Pixels	1.2 million
Response Time	25ms (Rising/Falling)
Viewing Angle (L/R/T/B)	70/70/50/70 degrees
Dimensions	7.67" x 5.19" x 1.38" / 195 x 132 x 35mm
Operating Temp	-4 ~ 158°F / -20 ~ 70°C
Touchscreen	x1 USB cable with VGA only; 5-wire resistive
HDMI	x1 Input
Composite	x2 RCA Inputs on cable with 3.5mm jack
VGA	x1 15-pin D-sub Input
Power	x1 2.1mm DC Input
Power Requirements	10 VDC to 27 VDC Input; 2A + pin; Negative Ground
Power Consumption	24 Watts (Max)
Weight	Net: 1.85 lbs / 0.84 kg Gross: 3.7 lbs / 1.68 kg

Specifications subject to change.