



LED-709HDM2

These high-definition, dual rack-mount monitors with touch-screen capability are designed for working in critical environments including video production and remote surveillance applications.

Benefits

- LED backlight: brighter picture using less power
- Displays HD signals (1080i/p and 720p)
- Built-in 5-wire resistive touch screen when viewing a VGA source

Related Products

- LED-709HD: 7" Field LCD Monitor w/ Plastic Case
- LED-709HDM: 7" LCD Monitor w/ Metal Case
- LED-709HDML: Flush-Mount LCD Monitor

Specifications	
Mount	3RU
HD Compatible	Yes (displays 1080p)
Anti Glare Coating	Yes
Case	Durable Metal
IR Remote Control	No
Native Aspect Ratio	16:9
Visible Screen Size (WH)	6" x 3.4" / 154.08 x 85.92mm
Resolution	1024 x 600
Brightness Rating	250 cd/m ² (Nit)
Contrast Ratio	700:1
Back Light	LED (20K)
Dot Pitch	0.0642(H) x 0.1790(V) mm
Number of Pixels	1.2M
Response Time	25ms (Rising/Falling)
Viewing Angle (L/R/T/B)	70/70/50/70 degrees
Dimensions	16.9" x 5.2" x 1.5" / 430 x 132 x 38mm
Operating Temp	-4 ~ 158°F / -20 ~ 70°C
Touchscreen	x1 USB cable with VGA only; 5-wire resistive
HDMI	x1 Input
Composite	x2 RCA Inputs on cable with 3.5mm jack
VGA	x1 15-pin D-sub Input
Power	x1 2.1mm DC Input
Power Requirements	10 VDC to 27 VDC Input; 2A + pin; Negative Ground
Power Consumption	24 Watts (Max)
Weight	Net: 6.15 lbs / 2.79 kg Gross: 10.45 lbs / 4.74 kg

Specifications subject to change.