



## LED-1213-IP

Commercial-grade 12" LED-backlit LCD monitor designed for continuously viewing ONVIF-compliant, IP-based cameras. Utilizing a secure, RISC-based architecture designed for viewing only, this monitor is ideal for use in sensitive environments where restricted network access needs to be maintained.

### Benefits

Secured On-screen display (OSD) menu requires logon credentials for making any user adjustments. Only power On/Off is allowed without credentials.

RISC-based architecture system that only offers viewing capability of network IP cameras; monitor is incapable of performing any other function.

Direct network or camera connection with 10M/100M self-adaptive LAN port

Each signal channel can set main stream and sub stream

Monitor supports up to four ONVIF-compliant IP cameras

### Accessories

WM-31: Fixed wall mount bracket

WM-302: 4-way pan/tilt wall mount bracket

### Specifications

<b>Mount</b>	VESA 100 x 100mm pattern; removable deskstand; (2) Keyholes
<b>Display</b>	12.1" TFT LCD
<b>Backlight</b>	LED
<b>Resolution</b>	1024 x 768; displays 1080i/p (1 CH), 720p (4CH)
<b>Viewable Area</b>	9.6" x 7.26" / 245.76 x 184.32mm
<b>Aspect Ratio</b>	4:3
<b>Brightness</b>	500 Nit
<b>Contrast</b>	700:1
<b>Display Colors</b>	16.2 million
<b>Response Time</b>	3 / 5ms (Rising / Falling)
<b>Viewing Angle</b>	80/80/80/80
<b>System Architecture</b>	RISC-based; Embedded Linux OS
<b>Wired Connectivity</b>	x1 RJ45 10M/100M self-adaptive LAN port
<b>Control Input</b>	Removable USB Optical Mouse (included)
<b>Video Input</b>	(4) View: 4x (1280x720) + sub (960x576) 720p (1) View 4x (1920x1080) + sub (960x576) 1080p
<b>Composite</b>	x1 RCA Input; x1 RCA Output
<b>RGB/VGA</b>	x1 15-pin D-sub Input
<b>HDMI</b>	x1 Input
<b>DVI</b>	x1 Input
<b>Storage</b>	External eSATA option; user-defined (secure)
<b>Audio</b>	x1 RCA L/R Input; x1 3.5mm Output
<b>USB Ports</b>	x2 USB2.0
<b>Power</b>	DC 12V Input
<b>Operating Temp</b>	32 ~ 104°F / 0 ~ 40°C
<b>Humidity</b>	20% ~ 90%
<b>Power Requirements</b>	Regulated 12VDC; 5 AMps, negative ground
<b>Power Supply</b>	Input: AC 100-240V, 50~60Hz, 0.8A; Output: DC 12V, 2A
<b>Power Consumption</b>	15 watts (Max)
<b>Dimensions w/Deskstand</b>	11.8" x 9.4" x 2.4" / 299.6 x 238.9 x 61.8mm
<b>Dimensions w/o Deskstand</b>	11.8" x 9.4" x 1.9" / 299.6 x 238.9 x 47mm
<b>Weight</b>	Net: 5lbs / 2.3kg Gross: 7.25lbs / 3.3kg

Specifications are subject to change.