



## LED-2703HDPVM

Commercial-grade, public view LCD monitor provides exceptional picture quality and image storage capability for displaying multiple content.

### Benefits

- Full HD (1080p/i) with no downscaling
- LED backlight: brighter picture using less power
- Camera captures and sends 1080p high definition image
- Simultaneous Camera Output via IP and Composite (CVBS)
- 3D Comb Filter and 3D De-Interlace for better picture quality
- Aesthetically designed and durable slim metal case with acrylic front face
- Advertising function; PIP/POP support for simultaneous camera and ad promotion
- Body Sensor for auto switch capability
- On-screen Warning Message - On/Off capable option
- Alternate Display between different channels - On/Off capable option
- Continuous warning beep when losing image
- Easy access to camera
- Remote Control included

### Specifications

<b>Mount</b>	VESA 100 x 100mm, 200 x 200mm
<b>Anti Glare Coating</b>	Yes
<b>Case</b>	Durable Metal, Acrylic Front Face
<b>IR Remote Control</b>	Yes
<b>Native Aspect Ratio</b>	16:9
<b>Visible Screen Size (WH)</b>	23.53" x 13.23" / 597.6 x 336mm
<b>Resolution</b>	1920 x 1080 (Full HD)
<b>Brightness Rating</b>	350 cd/m <sup>2</sup>
<b>Contrast Ratio</b>	3000:1
<b>Back Light</b>	LED (30K)
<b>Dot Pitch</b>	0.3(H) x 0.3(V) mm
<b>Color Depth</b>	16.7 million
<b>Response Time</b>	5ms (Rising/Falling)
<b>Viewing Angle (L/R/T/B)</b>	89/89/89/89 degrees
<b>Digital Signal Processing</b>	3D Comb Filter and 3D De-Interlace
<b>PIP / POP Dual Screens</b>	Yes
<b>Video Camera</b>	x1 RJ-45 Output, x1 BNC Output
<b>Camera Image Sensor</b>	1/2.8" SONY® Exmor
<b>Camera Resolution</b>	1920 x 1080 @ 25 frames per second
<b>Minimum Illumination</b>	0.1 Lux (Color), 0.01 Lux (B/W)
<b>Camera Compression</b>	H.264 MJPEG
<b>Camera Compliance</b>	ONVIF 2.2
<b>Camera Lens</b>	3.3-12mm Vari-focal, IR Corrected
<b>Card Storage</b>	x1 SD Card storage Input; Local Recording
<b>Composite</b>	x1 BNC Input; x1 BNC Output
<b>HDMI</b>	x1 Input
<b>VGA</b>	x1 Input
<b>Network</b>	x1 RJ-45 Port
<b>USB</b>	x1 Input
<b>Operating Temperature</b>	32 ~ 122°F / 0 ~ 50°C
<b>Power</b>	x1 24VDC Input
<b>Power Requirements</b>	100 ~ 240 VAC; 75 Hz
<b>Power Consumption</b>	<50 Watts
<b>Dimensions</b>	25.1" x 17.65" x 2.76" / 637.5 x 448.3 x 70.1mm
<b>Weight</b>	Net: 25 lbs / 11.3 kg

Specifications subject to change.