



## LED-5000-4K

Ultra High-definition (3840 x 2160) LCD monitor is designed for viewing 4K and HD cameras in 24/7 mission-critical environments. Ideal for use in security operation centers, high volume retail locations, and in casino surveillance hubs.

### Benefits

LED backlight: brighter picture using less power

Ultra-High Definition (3840 x 2160) displays 4K content with no downscaling; ability to upscale Full HD (1920 x 1080) to full screen

Very wide-viewing angle

ADA compliant slim design with < 3 inch depth

Removable deskstand

Built-in stereo speakers

### Accessories

WM-3742: Fixed 200x200mm VESA wall mount bracket

### Specifications

Mounting	VESA 200x200mm / 400x200mm; removable deskstand
Case	Durable Metal
Panel Type	50" TFT Active Matrix LCD Display
Backlight	LED (30K)
Native Aspect Ratio	16:9
Visible Screen Size	43.1 x 24.3 in. / 1095.8 x 616.4mm
Anti-glare Surface Coating	Yes
Resolution	3840(H) x 2160(V) (Ultra HD)
Contrast Ratio	4000:1
Brightness	400 cd/m <sup>2</sup>
Display Colors	1.073 billion
Refresh Rate	60 Hz
Response Time	8ms (Rising/Falling)
Pixel Pitch	0.2865 x 0.2865mm
Digital Signal Processor	3D Comb Filter, 3D noise reduction, and de-interlacing
Viewing Angle (L/R/T/B)	88/88/88/88 degrees
HDMI	x1 Input
DisplayPort	x1 Input
VGA	x1 15-pin D-Sub Input
DVI	x1 Input
Composite	x1 (RCA) Input
USB	x1 Input
Power	x1 AC Input
Audio	2 Speakers x 5 Watts (Stereo); x2 Inputs
IR Remote Control	Yes
Operating Temp	32-104° F / 0 - 40° C
Humidity	5% ~ 95%
Power Requirements	110 -240V AC
Power Consumption	130 Watts (Max)
Dimensions with Desk Stand	45.17" x 26.65" x 7.6" / 1147 x 677 x 197mm
Dimensions	45.17" x 26.26" x 2.5" / 1147 x 667 x 63mm
Weight	77 lbs / 35 Kg

Specifications subject to change.