



LED-4301-4K

Ultra High-definition (3840 x 2160) LCD monitor is designed for viewing 4K and HD cameras and video signals in 24/7 mission-critical environments. Ideal for use in security operation centers, high volume retail locations, and in casino surveillance hubs.

Benefits

- LED backlight: brighter picture using less power
- Ultra-High Definition (3840 x 2160) displays 4K content with no downscaling; ability to upscale Full HD (1920 x 1080) to full screen
- Very wide viewing angle
- Slim design with 2.5" depth; ADA compliant
- Metal case with removable deskstand
- Built-in speakers

Accessories

WM-3742: Fixed 200x200mm VESA wall mount bracket

Specifications

Mounting	VESA 200x200mm and 400x200mm; Removable Desk Stand
Case	Durable Metal
Panel Type	43" TFT Active Matrix LCD Display
Backlight	LED (30K)
Native Aspect Ratio	16:9
Visible Screen Size	37" x 21" / 939.8 x 533.4mm
Anti-glare Surface Coating	Yes
Resolution	3840(H) x 2160(V) (Ultra HD)
Contrast Ratio	1000:1
Brightness	350 cd/m ²
Display Colors	1.073 billion; 10-bit
Refresh Rate	60 Hz
Response Time	8ms (Rising/Falling)
Pixel Pitch	0.2451 x 0.2451mm
Digital Signal Processor	3D Comb Filter, 3D noise reduction, and de-interlacing
Viewing Angle (L/R/T/B)	89/89/89/89 degrees
Audio Power/Speakers	8 Ohm, 2 Speakers x 5 Watts
HDMI	x1 Input
DisplayPort	x1 Input
VGA	x1 15-pin D-Sub Input
DVI	x1 Input
Composite	x1 (RCA) Input
USB	x1 Input
Power	x1 AC Input
Audio	x2 3.5mm Inputs
IR Remote Control	Yes
Operating Temp	32-104° F / 0 - 40° C
Humidity	5% ~ 95%
Power Requirements	110 -240V AC
Power Consumption	47 Watts (Max)
Dimensions with Desk Stand	39" x 25" x 7.6" / 990.8 x 635.7 x 197mm
Dimensions	39" x 22.8" x 2.5" / 990.8 x 580.2 x 63.1mm
Weight	49.6 lbs / 22.5 Kg

Specifications subject to change.