



## LED-1002HD2

Two 9.7" rack-mount monitors feature the latest screen imaging technology for enhanced clarity and sharpness. Both analog and digital video will benefit by being viewed on these monitors, and they are the best match for displaying higher resolution megapixel images.

### Benefits

- LED backlight: brighter picture using less power
- Wide viewing angle
- Excellent contrast ratio
- Very fast response time
- Image enhancing: 3D Interlace comb filter, DNR, 4H filter
- Built-in stereo speakers
- Durable metal case

### Related Products

- LED-1003HDL: Flush mount
- LED-1003HDX: Free standing with no front controls
- LED-1003HDLX: Flush mount
- LED-1003HD: Single 9.7" monitor



Specifications	
<b>Mount</b>	Rack (5RU)
<b>HD Compatible</b>	Yes
<b>Anti Glare Coating</b>	Yes
<b>Case</b>	Metal
<b>Native Aspect Ratio</b>	4:3
<b>Visible Screen Size (WH)</b>	7.8" x 5.9" / 197.6 x 148.8mm
<b>Resolution</b>	1024(H) x 768(V)
<b>Brightness Rating</b>	400 cd/m <sup>2</sup> (Nit)
<b>Contrast Ratio</b>	1000:1
<b>Back Light</b>	LED (30K)
<b>PC Compatibility</b>	Yes
<b>Dot Pitch</b>	0.192 (H) x 0.192 (V)mm
<b>Color Depth</b>	262,144
<b>Number of Pixels</b>	786,432
<b>Response Time</b>	2ms / 2ms (Rising/Falling)
<b>Audio Power / Speakers</b>	2 Speakers x 2 Watts
<b>Viewing Angle (L/R/T/B)</b>	89/89/89/89 degrees
<b>DSP</b>	3D Interlace comb DNR, 4H filter
<b>Dimensions</b>	8.8" x 8.7" x 3" / 223 x 222 x 77mm
<b>Operating Temp</b>	32 ~ 104°F / 0 ~ 40°C
<b>Power Requirements</b>	12VDC; 2A; Negative Ground
<b>Power Consumption</b>	30 Watts (Max)
<b>Composite</b>	x1 BNC Input / x1 BNC Output (per monitor)
<b>VGA</b>	x1 15-pin mini D-sub Input (per monitor)
<b>HDMI</b>	x2 Inputs (per monitor)
<b>Audio</b>	x1 R/L RCA Input
<b>Power</b>	x1 2.1mm DC Input
<b>Weight</b>	Net: 3.75 lbs / 1.7 kg

Specifications subject to change.