



LED-1906HDMTL

High-definition, LED-backlit, flush mount monitor with TV tuner housed in a durable metal case with a front control membrane. Built for active use in public spaces, this monitor is versatile and effective for any commercial video application.

Benefits Control of the Control of t	
Displays HD signals (1080i/p and 720p)	
3D + 3D image processing with digital noise reduction	
Built-in ATSC / Clear QAM Tuner	
Durable Metal Housing	
Built-in speakers	
R remote control	
ncludes Hospitality Features: Maximum volume, Key Lock, Scan Lock, a Auto Reset which maintains Startup Channel, Power On Volume, and P On Source	

Related Products

LED-1906HDMTLX: Flush-mount version with no front controls

LCD-1906HDMTR: Rack-mount version

LCD-1906HDMT: Wall-mount version with removable deskstand

Specifications	
Mount	Flush Mount
Screen Panel	18.5" TFT Active Matrix
HD Compatible	Yes
Anti Glare Coating	Yes
Case	Durable Metal
IR Remote Control	Yes
Native Aspect Ratio	16:9
Visible Screen Size (WH)	16.1" x 9.1" / 409.8 x 230.4mm
Resolution	1366(H) x 768(V)
Brightness Rating	250 cd/m ²
Contrast Ratio	1000:1
Back Light	LED (30K)
Dot Pitch	0.30(H) x 0.30(V)mm
Color Depth	16.7M
Number of Pixels	1,049,088
Response Time	5ms (Rising/Falling)
Audio Power / Speakers	8 Ohm, 2 Speakers x 2 Watts
Viewing Angle (L/R/T/B)	85/85/80/80 degrees
3D Comb Filter	Yes
Operating Temp	6 ~ 104°F / -14 ~ 40°C
Humidity	10% ~ 90%
Power Requirements	100 ~ 240 VAC; 50/60 Hz
Power Consumption	< 25 Watts (Active); < 0.5 Watts (Stand-by)
TV (ATSC/QAM Digital Tuner)	x1 F Connector (Coax) Input
HDMI	x3 Inputs
VGA	x1 15-pin D-sub Input
Component	x1 RCA YPbPr Input
Composite	x2 RCA Inputs; x1 RCA Output
Audio	x1 RCA L/R Output; x1 3.5mm PC Input; x1 3.5mm Output; x1 Coaxial Digital Output
USB	x1 Input for firmware updates only
Power	x1 AC Input
Dimensions	19.06" x 13.39" x 1.93" / 484 x 340 x 50mm
Cut-out Dimensions	17.75" x 12" / 450.85 x 304.8mm
Weight	Net: 8.8 lbs / 4 kg; Gross: 12 lbs / 5.4 kg

Specifications subject to change.