



LED-711-4K2

Dual 7" LCD monitors with native 1920 x 1200 resolution are capable of displaying 4K/UHD imagery. These monitors are best suited for broadcast, medical, and pro photography/video applications.

Benefits

- LED backlight: brighter picture using less power
- Native 1920 x 1200 resolution; displays up to 4K (4096 x 2160p)
- Ultra wide viewing angle (89/89/89/89)
- Multiple software features including Peaking Filter (monochrome), Check Field (B/W/R/G/B), Center Mark, Safe Area, Under Scan / Over Scan, Ratio, DSLR Mode, Freeze, Flip (U/D/R/L), Noise Reduction, and Zoom (1.4x - 10x)

Related Products

- LED-711-4K: 7" 4K LCD Monitor with battery back options
- LED-711-4KL: 7" 4K flush-mount LCD Monitor

| Specifications | |
|-----------------------------|--|
| Mount | 3RU |
| HD Compatible | Yes (displays up to 2160p) |
| Anti Glare Coating | Yes |
| Case | Durable Metal |
| Native Aspect Ratio | 16:9 |
| Visible Screen Size (WH) | 5.95" x 3.7" / 151.2 x 94.5mm |
| Resolution | 1920 x 1200 |
| Brightness Rating | 450 cd/m ² (Nit) |
| Contrast Ratio | 1100:1 |
| Back Light | LED (50K) |
| Dot Pitch | 0.07875(H) x 0.7875(V) mm |
| Number of Pixels | 16.7 million colors |
| Response Time | 10ms Rising / 15ms Falling |
| Viewing Angle (L/R/T/B) | 89/89/89/89 degrees |
| HDMI (each display) | x1 Input; x1 Output (pass-through) |
| HDMI Supported Resolutions | 720 x 480i/p @59.94/60Hz up to 1920x1080psf @23.93 ~ 60Hz; 3840 x 2160p @24 ~ 30Hz; 4096 x 2160p @24Hz |
| Composite (each display) | x1 BNC Input; x1 BNC Output |
| Composite Supported Formats | NTSC-M/J/4.43; PAL B/G/HID/M/N; SECAM |
| Audio (each display) | x1 3.5mm Output |
| Power | x1 2.1mm DC Input |
| Operating Temp | 14 ~ 140°F / -10 ~ 60°C |
| Power Requirements | 12VDC 2A (9VDC ~ 24VDC) |
| Power Consumption | ≤ 11 Watts (Max) |
| Dimensions | 19" x 5.5" x 1.4" / 482.6 x 139.8 x 35.6mm |
| Weight | Net: 6.15 lbs / 2.79 kg |

Specifications subject to change.