



## LED-711-4K

7" LCD monitor with native 1920 x 1200 resolution is capable of displaying 4K/UHD imagery. This monitor is best suited for broadcast, medical, and pro photography applications.

### Benefits

LED backlight: brighter picture using less power

Native 1920 x 1200 resolution; displays up to 4K (4096 x 2160p)

Ultra wide viewing angle (89/89/89/89)

Multiple software features including Peaking Filter (monochrome), Check Field (B/W/R/G/B), Center Mark, Safe Area, Under Scan / Over Scan, Ratio, DSLR Mode, Freeze, Flip (U/D/R/L), Noise Reduction, and Zoom (1.4x - 10x)

Battery pack options available for mobility / field use

### Related Products

TB-709M: Protective nylon tote bag with sun shield, and neck strap for hands-free use

BP-711-970: Attachable battery back for Sony F970 battery (battery not included)

BP-711-LPE6: Attachable battery back for Canon LP-E6 battery (battery not included)

LED-711-4K2: Dual 7" 1920 x 1200 rack-mount LCD Monitors

LED-711-4KL: 7" 1920 x 1200 flush-mount LCD monitor

### Specifications

<b>Mount</b>	VESA 75 x 75mm
<b>HD Compatible</b>	Yes (displays up to 2160p)
<b>Anti Glare Coating</b>	Yes
<b>Case</b>	Durable Metal
<b>Native Aspect Ratio</b>	16:9
<b>Visible Screen Size (WH)</b>	5.95" x 3.7" / 151.2 x 94.5mm
<b>Resolution</b>	1920 x 1200
<b>Brightness Rating</b>	450 cd/m <sup>2</sup> (Nit)
<b>Contrast Ratio</b>	1100:1
<b>Back Light</b>	LED (50K)
<b>Dot Pitch</b>	0.07875(H) x 0.7875(V) mm
<b>Number of Pixels</b>	16.7 million colors
<b>Response Time</b>	10ms Rising / 15ms Falling
<b>Viewing Angle (L/R/T/B)</b>	89/89/89/89 degrees
<b>HDMI</b>	x1 Input; x1 Output (loop-through)
<b>HDMI Supported Resolutions</b>	720 x 480i/p @59.94/60Hz up to 1920x1080psf @23.93 ~ 60Hz; 3840 x 2160p @24 ~ 30Hz; 4096 x 2160p @24Hz
<b>Composite</b>	x1 BNC Input; x1 BNC Output
<b>Composite Supported Formats</b>	NTSC-M/J/4.43; PAL B/G/HID/M/N; SECAM
<b>Audio</b>	x1 3.5mm Output
<b>Power</b>	x1 2.1mm DC Input
<b>Operating Temp</b>	14 ~ 140°F / -10 ~ 60°C
<b>Power Requirements</b>	12VDC 2A (9VDC ~ 24VDC)
<b>Power Consumption</b>	≤ 11 Watts (Max)
<b>Dimensions</b>	7.48" x 5.5" x 1.4" / 190 x 139.8 x 35.6mm
<b>Weight</b>	Net: 1.85 lbs / 0.84 kg

Specifications subject to change.