



## LED-711-4KL

7" flush-mount LCD monitor with native 1920 x 1200 resolution is capable of displaying 4K/UHD imagery. This monitor is best suited for broadcast, medical, and professional exhibition applications.

### Benefits

LED backlight: brighter picture using less power

Native 1920 x 1200 resolution; displays up to 4K (4096 x 2160p)

Ultra wide viewing angle (89/89/89/89)

Multiple software features including Peaking Filter (monochrome), Check Field (B/W/R/G/B), Center Mark, Safe Area, Under Scan / Over Scan, Ratio, DSLR Mode, Freeze, Flip (U/D/R/L), Noise Reduction, and Zoom (1.4x - 10x)

### Related Products

LED-711-4K2: Dual 7" 1920 x 1200 rack-mount LCD Monitors

LED-711-4K: 7" 1920 x 1200 LCD monitor displays 4K

Specifications	
Mount	Flush-mount
HD Compatible	Yes (displays up to 2160p)
Anti Glare Coating	Yes
Case	Durable Metal
Native Aspect Ratio	16:9
Visible Screen Size (WH)	5.95" x 3.7" / 151.2 x 94.5mm
Resolution	1920 x 1200
Brightness Rating	450 cd/m <sup>2</sup> (Nit)
Contrast Ratio	1100:1
Back Light	LED (50K)
Dot Pitch	0.07875(H) x 0.7875(V) mm
Number of Pixels	16.7 million colors
Response Time	10ms Rising / 15ms Falling
Viewing Angle (L/R/T/B)	89/89/89/89 degrees
HDMI	x1 Input; x1 Output (loop-through)
HDMI Supported Resolutions	720 x 480i/p @59.94/60Hz up to 1920x1080psf @23.93 ~ 60Hz; 3840 x 2160p @24 ~ 30Hz; 4096 x 2160p @24Hz
Composite	x1 BNC Input; x1 BNC Output
Composite Supported Formats	NTSC-M/J/4.43; PAL B/G/HID/M/N; SECAM
Audio	x1 3.5mm Output
Power	x1 2.1mm DC Input
Operating Temp	14 ~ 140°F / -10 ~ 60°C
Power Requirements	12VDC 2A (9VDC ~ 24VDC)
Power Consumption	≤ 11 Watts (Max)
Dimensions	9.05" x 7.08" x 1.4" / 230 x 179.8 x 35.6mm
Cut-out Dimensions	7.48" x 5.5" / 190 x 139.8mm
Weight	Net: 1.85 lbs / 0.84 kg

Specifications subject to change.