



LED-1562HDX

15.6" LED-backlit, LCD monitor with no front controls, has optimal picture quality with native Full HD resolution (1920 x 1080). This latest generation model is ideal for any small screen, high quality video installations.

Benefits

- Displays native Full HD signals (1080i/p) with no downscaling
- LED backlight: brighter picture using less power
- Widescreen (16:9) native aspect ratio
- Multiple connections including HDMI, VGA and RS-232
- Built-in removable desk stand
- Built-in speakers

Related Products

- LED-1562HD: 15.6" HD LCD monitor with HDMI, RS-232, VGA, and USB
- LED-1562HDL: Flush-mount version of LED-1562HD
- LED-1566HDLX: Flush-mount version of LED-1562HDX (no front controls)
- LED-1562HDR: Rack-mount version of LED-1562HD

Specifications	
Mount	VESA 75 x 75mm; removable desk stand
HD Compatible	Yes
Anti Glare Coating	Yes
Case	Durable Metal
IR Remote Control	Yes
Native Aspect Ratio	16:9
Visible Screen Size (WH)	13.6" x 7.6" / 344.16 x 193.59mm
Resolution	1920(H) x 1080(V) (Full HD)
Brightness Rating	300 cd/m ² (Nit)
Contrast Ratio	600:1
Back Light	LED (30K)
Dot Pitch	0.17925(H) x 0.17925(V)mm
Color Depth	6-bit, 262K
Number of Pixels	2,073,600
Response Time	8ms (Rising/Falling)
Audio Power / Speakers	8 Ohm, 2 Speakers x 5 Watts
Viewing Angle (L/R/T/B)	70/70/60/60 degrees
Digital Signal Processor	3D Comb Filter
HDMI	x2 Inputs
Composite	x1 BNC Input; x1 Output
PC	x1 15-pin mini D-sub Input
RS-232	x1 Input
Audio	x1 RCA L/R Input / x1 3.5mm PC Input
Power	x1 2.1mm DC Input
Power Requirements	Regulated 12VDC; 3A; Negative Ground
Power Consumption	8 Watts (Max)
Operating Temp	32 ~ 104°F / 0 ~ 40°C
Humidity	10% ~ 90%
Dimensions	16.22" x 11.69" x 1.85" / 412 x 297 x 47mm
Weight	Net: 5.9 lbs / 2.7 kg

Specifications subject to change.