



## LED-1910HDVBR

This LED-backlit monitor with sunlight readability is housed in a rack-mount and features the latest technology with enhanced picture clarity and sharpness for both analog and digital video signals.

### Benefits

- High brightness enables clear viewing in direct sunlight areas
- Analog video is very clear with no detail loss
- 3D Comb Filter for better picture quality
- High contrast ratio for better picture definition
- Durable metal case housing

### Accessories

- WM-32: Fixed Wall mount bracket
- WM-302: Wall mount with swing arm & 4-way adjustable

| Specifications           |  |
|--------------------------|--|
| Mount                    | 8RU rack-mount   |
| HD Compatible            | Yes  |
| Anti Glare Coating       | Yes  |
| Case                     | Durable Metal Housing                                  |
| IR Remote Control        | Yes  |
| Native Aspect Ratio      | 5:4  |
| Visible Screen Size (WH) | 14.81" x 11.85" / 376.32 x 301.06mm                    |
| Resolution               | 1280(H) x 1024(V)                                      |
| Brightness Rating        | 1,000 cd/m <sup>2</sup>                                |
| Contrast Ratio           | 1000:1   |
| Back Light               | LED (30K)  |
| Dot Pitch                | 0.294(H) x 0.294(V)mm                                  |
| Color Depth              | 16.7 million   |
| Number of Pixels         | 1,310,720  |
| Response Time            | 5ms (Rising/Falling)                                   |
| Audio Power / Speakers   | 2 Speakers x 2.5 Watts                                 |
| Viewing Angle (L/R/T/B)  | 85/85/80/80 degrees                                    |
| Digital Signal Processor | 3D Comb Filter and noise reduction                     |
| Dimensions               | 19" x 13.5" x 2" / 482.6 x 343 x 50.8mm                |
| Operating Temp           | 32 ~ 122°F / 0 ~ 50°C                                  |
| Humidity                 | 5% ~ 90%   |
| Power Requirements       | 12 VDC (Includes ext. AC adapter)                      |
| Power Consumption        | <20 Watts  |
| Composite                | x2 BNC Inputs / Outputs                                |
| VGA                      | x1 Input   |
| HDMI                     | x1 Input   |
| S-Video                  | x1 Input   |
| Audio                    | x2 Inputs  |
| Power                    | x1 2.1mm DC Input                                      |
| Weight                   | Net: 8.07 lbs / 3.66 kg;<br>Gross: 19.75 lbs / 8.96 kg |

Specifications subject to change.

