



## LED-2704HDPVM

Commercial-grade, 27 inch public view LCD monitor provides exceptional picture quality.

### Benefits

- Full HD (1080p/i) with no downscaling
- LED backlight: brighter picture using less power
- Camera captures and sends 1080p high definition image
- Simultaneous Camera Output via IP and Composite (CVBS)
- 3D Comb Filter and 3D De-Interlace for better picture quality
- Aesthetically designed and durable slim metal case with acrylic front face
- Body Sensor for auto switch capability
- On-screen Warning Message - On/Off capable option
- Alternate Display between different channels - On/Off capable option
- Continuous warning beep when losing image
- Easy access to camera
- Remote Control included

### Related Products

LED-1011HDPVM: 10" LCD Public View Monitor with IP Camera

Specifications	
Mount	VESA 100 x 100mm
Anti Glare Coating	Yes
Case	Durable Metal, Acrylic Front Face
IR Remote Control	Yes
Native Aspect Ratio	16:9
Visible Screen Size (WH)	23.53" x 13.23" / 597.6 x 336mm
Resolution	1920 x 1080 (Full HD)
Brightness Rating	350 cd/m <sup>2</sup>
Contrast Ratio	3000:1
Back Light	LED (30K)
Dot Pitch	0.3(H) x 0.3(V) mm
Color Depth	16.7 million
Response Time	5ms (Rising/Falling)
Viewing Angle (L/R/T/B)	89/89/89/89 degrees
Digital Signal Processing	3D Comb Filter and 3D De-Interlace
Video Camera	x1 RJ-45 Output, x1 BNC Output
Camera Image Sensor	1/2.8" SONY® Exmor
Camera Resolution	1920 x 1080 @ 25 frames per second
Minimum Illumination	0.1 Lux (Color), 0.01 Lux (B/W)
Camera Compression	H.264 MJPEG
Camera Compliance	ONVIF 2.2
Camera Lens	3.3-12mm Vari-focal, IR Corrected
SD Card Slot	x1 SD Card Input; plays stored media
Composite	x1 BNC Input; x1 BNC Output
HDMI	x1 Input
VGA	x1 Input
Network	x1 RJ-45 Port
USB	x1 Input
Operating Temperature	32 ~ 122°F / 0 ~ 50°C
Power	x1 24VDC Input
Power Requirements	100 ~ 240 VAC; 75 Hz
Power Consumption	<50 Watts
Dimensions	25.1" x 17.65" x 2.76" / 637.5 x 448.3 x 70.1mm
Weight	Net: 25 lbs / 11.3 kg

Specifications subject to change.