



## LED-1906HDMTX

High-definition, LED-backlit, mid-size monitor with digital TV tuner and no front controls is ideal for use in any public or controlled environment that requires a quality and durable video display.

### Benefits

- Displays HD signals (1080i/p and 720p)
- 3D + 3D image processing with digital noise reduction
- Built-in ATSC / Clear QAM digital TV Tuner
- Durable Metal Housing
- Built-in speakers
- Built-in removable deskstand
- IR remote control

### Accessories

- DS-1906M: Desk stand for LED-1906HDMT
- HM-401: Under-cabinet hinge mount
- WM-32: Wall mount bracket (fixed/tilting)
- WM-302: Wall mount with swing arm & 4-way adjustable
- WMC-2346: Ceiling mount bracket for 1.5" NPT pipe

### Related Products

- LED-1906HDMT: Stand-alone version with front controls
- LED-1906HDMTL: Flush-mount version
- LED-1906HDMTLX: Flush-mount version with no front controls
- LED-1906HDMTR: Rack-mount version



Specifications	
Mount	VESA 75 x 75mm
Screen Panel	18.5" TFT Active Matrix
HD Compatible	Yes (displays 1080i/p)
Anti Glare Coating	Yes
Case	Durable Metal
IR Remote Control	Yes
Native Aspect Ratio	16:9
Visible Screen Size (WH)	16.1" x 9.1" / 409.8 x 230.4mm
Resolution	1366 x 768
Brightness Rating	230 cd/m <sup>2</sup> (Nit)
Contrast Ratio	1000:1
Back Light	LED
Dot Pitch	0.30(H) x 0.30(V)mm
Color Depth	16.7M
Number of Pixels	1,049,088
Response Time	5ms (Rising/Falling)
Audio Power / Speakers	8 Ohm, 2 Speakers x 2 Watts
Viewing Angle (L/R/T/B)	85/85/80/80 degrees
3D Comb Filter	Yes
Digital TV Tuner	ATSC/Clear QAM Tuner
Dimensions	18.5" x 14.25" x 1.4" / 469 x 362 x 36mm
Operating Temp	6 ~ 104°F / -14 ~ 40°C
Power Requirements	100 ~ 240 VAC; 50/60Hz
Power Consumption	<25 Watts; <= 0.5 Watts (Stand-by)
HDMI	x3 Inputs
Component	x1 RCA YPbPr Input
Composite	x2 RCA Inputs; x1 RCA Output
VGA (RGB)	x1 15-pin mini D-sub Input
TV (RF)	x1 F (Coax) Input
Audio	x1 RCA L/R Output; x1 3.5mm earphone Output
Weight	Net: 8.8 lbs / 4 kg; Gross: 11 lbs / 5 kg

Specifications subject to change.