



LED-1003HDL

This 9.7" flush mount monitor features the latest screen imaging technology for enhanced clarity and sharpness. Both analog and digital video will benefit by being viewed on this monitor, and it is the best match for displaying higher resolution megapixel imagery.

Benefits

- LED backlight: brighter picture using less power
- Wide viewing angle
- Excellent contrast ratio
- Very fast response time
- Image enhancing: 3D Interlace comb filter, DNR, 4H filter
- Durable metal case

Related Products

- LED-1002HDM: 9.7" flush-mount monitor with RS-232 and Gorilla Glass
- LED-1003HDLX: 9.7" flush-mount monitor with no front controls
- LED-1003HD: 9.7" free-standing monitor
- LED-1003HDX: 9.7" free-standing monitor with no front controls

Specifications	
Mount	Flush Mount
HD Compatible	Yes
Anti Glare Coating	Yes
Case	Metal
Native Aspect Ratio	4:3
Visible Screen Size (WH)	7.8" x 5.9" / 197.6 x 148.8mm
Resolution	1024(H) x 768(V)
Brightness Rating	400 cd/m ² (Nit)
Contrast Ratio	1000:1
Back Light	LED (30K)
PC Compatibility	Yes
Dot Pitch	0.192(H) x 0.192(V)mm
Color Depth	262,144
Number of Pixels	786,432
Response Time	20ms / 20ms (Rising/Falling)
Audio Power / Speakers	x2 Speakers
Viewing Angle (L/R/T/B)	89/89/89/89 degrees
Installer's Cut Out	8 3/4" x 7 3/4" / 223 x 196.4mm
3D Comb Filter	3D Interlace & DNR, 4H filter
Dimensions	10.8" x 9.8" x 1.85" / 274.3 x 248 x 46.99mm
Operating Temp	32 ~ 104°F / 0 ~ 40°C
Power Requirements	12VDC; 1A; Negative Ground
Power Consumption	30 Watts (Max)
HDMI	x1 Input
VGA	x1 15-pin D-sub Input
Composite	x1 BNC Input; 1x BNC Output
Audio	x1 RCA L/R Input; x1 3.5mm PC Input
Power	x1 2.1mm DC Input
Weight	Net: 3.3 lbs / 1.5 kg; Gross: 5.4 lbs / 2.4 kg

Specifications subject to change.