



## LED-1709HDR

This LED-backlit rack monitor features the latest technology with enhanced picture clarity and sharpness for both analog and digital video signals.

### Benefits

- Analog video is very clear with no detail loss
- Displays 1080i/p digital video
- 3D Comb Filter for better picture quality
- High contrast ratio for better picture definition
- Durable metal case

### Related Products

- LED-1709HD - 17" LCD monitor with tilting desk stand; wall mountable
- LED-1709HDL - 17" LCD monitor in flush-mount
- LED-1908HD - 19" LCD monitor with tilting desk stand; wall mountable
- LED-1908HDL - 19" LCD monitor in flush-mount for in-wall mounting
- LED-1908HDR - 19" LCD monitor in 19" rack-mount
- LED-1910HDVB - 19" High Brightness LCD monitor; wall mountable

### Specifications

<b>Mount</b>	Rack (8RU)
<b>HD Compatible</b>	Yes
<b>Anti Glare Coating</b>	Yes
<b>Case</b>	Durable Metal
<b>Native Aspect Ratio</b>	5:4
<b>Visible Screen Size (WH)</b>	13.4" x 10.7" / 340 x 272mm
<b>Resolution</b>	1280(H) x 1024(V)
<b>Brightness Rating</b>	250 cd/m <sup>2</sup>
<b>Contrast Ratio</b>	1000:1
<b>Back Light</b>	LED (30K)
<b>Dot Pitch</b>	0.264(H) x 0.264(V)mm
<b>Color Depth</b>	16.7M
<b>Number of Pixels</b>	1,310,720
<b>Response Time</b>	5ms (Rising/Falling)
<b>Audio Power / Speakers</b>	x2 1.5 Watts
<b>Viewing Angle (L/R/T/B)</b>	85/85/80/80 degrees
<b>Digital Signal Processor</b>	3D Comb Filter
<b>HDMI</b>	x2 Inputs
<b>Composite</b>	x1 BNC Input; x1 BNC Output
<b>VGA</b>	x1 VGA 15-pin D-sub Input
<b>Audio</b>	x1 L/R RCA Input; x1 3.5 PC stereo Input
<b>Power</b>	x1 2.1mm DC Input
<b>Power Requirements</b>	DC 12V (AC100~240)[50/60]
<b>Power Consumption</b>	20 Watts (Max)
<b>Operating Temp</b>	32 ~ 104°F / 0 ~ 40°C
<b>Humidity</b>	10% ~ 90%
<b>Dimensions</b>	8RU x 2.9"
<b>Weight</b>	Net: 11.9 lbs / 5.4 kg; Gross: 17.5 lbs / 8 kg

Specifications subject to change.