



LED-2156HDVB

21.5" LED-backlit LCD monitor with sunlight visible screen has optimal picture quality with native Full HD resolution (1920 x 1080). This model is designed for industrial 24x7 use, and it is ideal for any small screen, high quality video installations.

Benefits

- Displays native Full HD signals (1080i/p) with no downscaling
- 1500 Nit Brightness
- LED backlight: brighter picture using less power
- Widescreen (16:9) native aspect ratio
- Multiple connections including HDMI, VGA, and RS-232

Specifications	
Mount	VESA 100 x 100mm
Case	Durable Metal
IR Remote Control	Yes
Native Aspect Ratio	16:9
Resolution	1920(H) x 1080(V) (Full HD)
Brightness Rating	1,500 cd/m ² (Nit)
Contrast Ratio	3000:1
Back Light	LED (40K)
Color Depth	16.7 million colors
Pixel Pitch	0.24795 x 0.24795mm
Response Time	25 milliseconds
Audio Power / Speakers	2 Speakers x 5 Watts
Viewing Angle (L/R/T/B)	89/89/89/89 degrees
Digital Signal Processor	3D Comb Filter
HDMI	x2 Inputs
VGA	x1 15-pin mini D-sub Input
RS-232	x1 port
Audio	x1 3.5mm PC Input
SD Slot	x1 Slot
Power	x1 2.1mm DC Input
Power Requirements	Regulated 12VDC; Negative Ground
Power Consumption	<35 Watts (Max)
Operating Temp	32 ~ 104°F / 0 ~ 40°C
Humidity	10% ~ 90%
Dimensions	19.7" x 12.2" x 3.3"; 500 X 310 X 85mm
Weight	13.2 lbs / 5.98 Kgs
Certifications	FCC-DOC, CE, ROHS

Specifications subject to change.

