



LED-1003HD

This 9.7" LED-backlit monitor features the latest screen imaging technology for enhanced clarity and sharpness. Both digital and analog video will benefit by being viewed on this monitor; it is the best match for displaying higher resolution mega-pixel imagery.

Benefits

- LED backlight: brighter picture using less power
- Wide viewing angle
- Excellent contrast ratio
- Very fast response time
- Image enhancing: 3D Interlace comb filter, DNR, 4H filter
- Durable metal case

Accessories

- DC-1500: Factory approved car cord
- WM-32: Wall mount bracket (fixed/tilting)
- WM-302: Wall mount with swing arm & 4-way adjustable

Related Products

- LED-1002HD2: Dual 9.7" monitors in a rack-mount
- LED-1003HDL: 9.7" monitor in a flush-mount
- LED-1003HDX: 9.7" free-standing monitor with no front controls
- LED-1003HDLX: 9.7" flush-mount monitor with no front controls

Specifications

| | |
|---------------------------------|--|
| Mount | VESA 75x75mm and 100x100mm; ¼ - 20 pad on top; Removable Deskstand |
| HD Compatible | Yes |
| Anti Glare Coating | Yes |
| Case | Metal |
| Native Aspect Ratio | 4:3 |
| Visible Screen Size (WH) | 7.8" x 5.9" / 197.6 x 148.8mm |
| Resolution | 1024(H) x 768(V) |
| Brightness Rating | 400 cd/m ² (Nit) |
| Contrast Ratio | 1000:1 |
| Back Light | LED (30K) |
| PC Compatibility | Yes |
| Dot Pitch | 0.192 (H) x 0.192 (V)mm |
| Color Depth | 262,144 |
| Number of Pixels | 786,432 |
| Response Time | 20ms / 20ms (Rising/Falling) |
| Audio Power / Speakers | 2 Speakers x 2 Watts |
| Viewing Angle (L/R/T/B) | 89/89/89/89 degrees |
| 3D Comb Filter | 3D Interlace comb DNR, 4H filter |
| Dimensions w/ Deskstand | 8.8" x 7.7" x 6.3" / 223 x 196.4 x 160mm |
| Dimensions | 8.8" x 7.7" x 1.85" / 223 x 196.4 x 47mm |
| Operating Temp | 32 ~ 104°F / 0 ~ 40°C |
| Power Requirements | 12VDC; 1A; Negative Ground |
| Power Consumption | 30 Watts (Max) |
| HDMI | x2 Inputs |
| VGA | x1 15-pin mini D-sub Input |
| Composite | x1 BNC Input; 1x Output |
| Audio | x1 RCA L/R Input; x1 3.5mm PC Input |
| Power | x1 2.1mm DC Input |
| Weight | Net: 2.55 lbs / 1.2 kg; Gross: 4.6 lbs / 2.1 kg |

Specifications subject to change.