



LED-1906HDMT

High-definition, LED-backlit, mid-size LCD monitor housed in a durable metal case with a front control membrane. Built for active use in public spaces, this monitor is versatile and effective for any commercial video application.

Benefits

- Displays HD signals (1080i/p)
- 3D + 3D image processing with digital noise reduction
- Built-in ATSC / Clear QAM Tuner
- Durable Metal Housing
- Built-in speakers
- 75mm VESA pattern for mounting
- IR remote control
- Includes Hospitality Features: Maximum volume, Key Lock, Scan Lock, and Auto Reset which maintains Startup Channel, Power On Volume, and Power On Source

Accessories

- DS-1906M: Desk stand for LED-1906HDMT
- WM-32: Wall mount bracket (fixed/tilting)
- WM-302: Wall mount with swing arm & 4-way adjustable
- WMC-2346: Ceiling mount bracket for 1.5" NPT pipe

Related Products

- LED-1906HDMTL: Flush mount version
- LED-1906HDMTR: Rack mount version

Specifications	
Mount	VESA 75 x 75mm
Screen Panel	18.5" TFT Active Matrix
HD Compatible	Yes
Anti Glare Coating	Yes
Case	Durable Metal
IR Remote Control	Yes
Native Aspect Ratio	16:9
Visible Screen Size (WH)	16.1" x 9.1" / 409.8 x 230.4mm
Resolution	1366(H) x 768(V)
Brightness Rating	250 cd/m ² (Nit)
Contrast Ratio	1000:1
Back Light	LED (30K)
Dot Pitch	0.30(H) x 0.30(V)mm
Color Depth	16.7M
Number of Pixels	1,049,088
Response Time	5ms (Rising/Falling)
Audio Power / Speakers	8 Ohm, 2 Speakers x 2 Watts
Viewing Angle (L/R/T/B)	85/85/80/80 degrees
Digital Signal Processing	3D comb filter image processing and 3D digital noise reduction
Dimensions	17.51" x 11.89" x 1.4" / 445 x 302 x 36mm
Operating Temp	6 ~ 104°F / -14 ~ 40°C
Power Requirements	100 ~ 240 VAC; 50/60Hz
Power Consumption	<25 Watts; <= 0.5 Watts (Stand-by)
TV (ATSC/QAM Digital Tuner)	x1 F (Coax) Input
HDMI	x2 Inputs
VGA (RGB)	x1 15-pin mini D-sub Input
Composite	x1 RCA Input
USB	x1 Input for firmware updates only
Audio	x1 RCA L/R Input; x1 3.5mm earphone Output
Weight	Net: 8.8 lbs / 4 kg; Gross: 11 lbs / 5 kg

Specifications subject to change.