



LED-1906HDMTLX

High-definition, LED-backlit, flush-mount monitor with digital TV tuner and no front controls. Designed for active use in public spaces, this monitor is versatile and effective for any commercial video application.

Benefits

- LED backlight: brighter picture using less power
- Displays HD signals (1080i/p and 720p)
- 3D + 3D image processing with digital noise reduction
- Built-in ATSC / Clear QAM Tuner
- Durable Metal Housing
- Built-in speakers
- IR remote control is included for use since there are no front controls; ideal for use in public spaces.
- Includes Hospitality Features: Maximum volume, Key Lock, Scan Lock, and Auto Reset which maintains Startup Channel, Power On Volume, and Power On Source

Related Products

- LED-1906HDMTR: Rack-mount version
- LED-1906HDMTL: Flush-mount version
- LED-1906HDMT: Wall-mount version with removable deskstand
- LED-1906HDMTX: Wall-mount version with removable deskstand and no front controls

Specifications	
Mount	Flush Mount
HD Compatible	Yes
Anti Glare Coating	Yes
Screen Panel	18.5" TFT Active Matrix
Case	Durable Metal
IR Remote Control	Yes
Native Aspect Ratio	16:9
Visible Screen Size (WH)	16.1" x 9.1" / 409.8 x 230.4mm
Resolution	1366(H) x 768(V)
Brightness Rating	250 cd/m ²
Contrast Ratio	1000:1
Back Light	LED (30K)
Dot Pitch	0.30(H) x 0.30(V)mm
Color Depth	16.7 million
Number of Pixels	1,049,088
Response Time	5ms (Rising/Falling)
Audio Power / Speakers	8 Ohm, 2 Speakers x 2 Watts
Viewing Angle (L/R/T/B)	85/85/80/80 degrees
3D Comb Filter	Yes
TV (ATSC/QAM Digital Tuner)	x1 F Connector (Coax) Input
HDMI	x2 Inputs
VGA	x1 15-pin D-sub Input
USB	x1 Input for firmware updates only
Composite	x1 RCA Input
Audio	x1 RCA L/R Input; x1 3.5mm Output
Power	x1 AC Input
Operating Temp	6 ~ 104°F / -14 ~ 40°C
Humidity	10% ~ 90%
Power Requirements	100 ~ 240 VAC; 50/60 Hz
Power Consumption	< 25 Watts (Active); < 0.5 Watts (Stand-by)
Dimensions	19.06" x 13.39" x 1.93" / 484 x 340 x 50mm
Cut-Out Dimensions	17.75" x 12" / 440.85 x 304.5mm
Weight	Net: 8 lbs / 3.6 kg; Gross: 11.2 lbs / 5.1 kg

Specifications subject to change.