



## LED-1566HDTL

15.6" LED-backlit LCD monitor in a flush-mount has a built-in ATSC/QAM digital TV tuner has optimal picture quality with native Full HD resolution (1920 x 1080). This latest generation model is ideal for any small screen, high quality video installations.

### Benefits

- LED backlight: brighter picture using less power
- Displays native Full HD signals (1080i/p) with no downscaling
- Widescreen (16:9) native aspect ratio
- Hotel TV Functions: default input source, default TV channel, max volume, keypad lock, and cloning through USB
- Multiple connections including HDMI, VGA, and USB
- Built-in speakers

### Related Products

- LED-1566HDT: 15.6" stand alone LCD TV / monitor with removable desk stand
- LED-1566HDTR: 15.6" rack mount LCD TV / monitor

Specifications	
Mount	Flush-mount
HD Compatible	Yes
Anti Glare Coating	Yes
Case	Durable ABS Plastic
IR Remote Control	Yes
Native Aspect Ratio	16:9
Visible Screen Size (WH)	13.6" x 7.6" / 345 x 195mm
Resolution	1920(H) x 1080(V) (Full HD)
Brightness Rating	300 cd/m <sup>2</sup> (Nit)
Contrast Ratio	800:1
Back Light	LED (15K)
Dot Pitch	0.215(H) x 0.215(V)mm
Color Depth	16.7M
Number of Pixels	2,073,600
Response Time	25ms (Rising/Falling)
Audio Power / Speakers	8 Ohm, 2 Speakers x 5 Watts
Viewing Angle (L/R/T/B)	85/85/85/85 degrees
3D Comb Filter	Yes
Dimensions	16.7" x 11.4" x 1.9" / 425 x 290 x 48mm
Operating Temp	32 ~ 104°F / 0 ~ 40°C
Humidity	10% ~ 90%
Power Requirements	Regulated 12VDC; 3A; Negative Ground
Power Consumption	Active 30 Watts (Max)
ATSC/QAM Digital Tuner	x1 RF Input
HDMI	x1 Input
VGA	x1 15-pin D-sub
Composite	x1 RCA Input
Component	x1 RCA (3) Inputs
USB	x1 Input
Audio	x1 RCA L/R Input and Output; x1 3.5mm PC Input
Power	x1 2.1mm DC Input
Cut-out Dimensions	15" x 9.6"
Weight	Net: 2.6 lbs / 1.18 kg; Gross: 4.9 lbs / 2.2 kg

Specifications subject to change.