



LED-1709HD

This industrial-grade monitor features the latest technology with enhanced picture clarity and sharpness for both analog and digital video signals.

Benefits

- Analog video is very clear with no detail loss
- Displays 1080i/p digital video
- 3D Comb Filter for better picture quality
- High contrast ratio for better picture definition
- Durable metal case

Accessories

- WM32: Wall-mount Bracket
- WM-302: 4-way VESA wall mount with swing arm

Specifications

Mount	VESA 100mm x 100mm; Removable Deskstand
HD Compatible	Yes
Anti Glare Coating	Yes
Case	Durable Metal
Native Aspect Ratio	5:4 (4:3 available)
Visible Screen Size (WH)	13.4" x 10.7" / 340 x 272mm
Resolution	1280 x 1024
Brightness Rating	250 cd/m ²
Contrast Ratio	1000:1
Back Light	LED
Dot Pitch	0.264(H) x 0.264(V)mm
Color Depth	16.7M
Number of Pixels	1,310,720
Response Time	5ms (Rising/Falling)
Audio Power / Speakers	2 Speakers x 1.5 Watts
Viewing Angle (L/R/T/B)	85/85/80/80 degrees
3D Comb Filter	Yes
HDMI	x2 Inputs
Composite	x1 BNC Input; x1 Output
VGA	x1 15-pin D-sub Input
Audio	x1 L/R RCA Input; x1 3.5 PC stereo Input
Power	x1 2.1mm DC Input
Power Requirements	DC 12V (AC100~240)[50/60Hz]
Power Consumption	20 Watts (Max)
Operating Temp	32 ~ 122°F / 0 ~ 50°C
Storage Temp	-4 ~ 149°F / -20 ~ 65°C
Humidity	10% ~ 95%
Dimensions	14.9" x 13.1" x 2.9" / 378 x 331.5 x 72mm
Weight	Net: 9.95 lbs / 4.5 kg; Gross: 15.5 lbs / 7 kg

Specifications subject to change.