



LED-1709HDL

This LED-backlit flush monitor features the latest technology with enhanced picture clarity and sharpness for both analog and digital video signals.

Benefits

- Analog video is very clear with no detail loss
- Displays 1080i/p digital video
- 3D Comb Filter for better picture quality
- High contrast ratio for better picture definition
- Durable metal case

Related Products

- LED-1709HD - 17" LCD monitor with tilting desk stand; wall mountable
- LED-1709HDR - 17" LCD monitor in 19" rack-mount
- LED-1908HD - 19" LCD monitor with tilting desk stand; wall mountable
- LED-1908HDL - 19" LCD monitor in flush-mount for in-wall mounting
- LED-1908HDR - 19" LCD monitor in 19" rack-mount
- LED-1910HDVB - 19" High Brightness LCD monitor; wall mountable

Specifications

| | |
|---------------------------------|--|
| Mount | Flush Mount |
| HD Compatible | Yes |
| Anti Glare Coating | Yes |
| Case | Durable Metal |
| Native Aspect Ratio | 5:4 |
| Visible Screen Size (WH) | 13.4" x 10.7" / 340 x 272mm |
| Resolution | 1280(H) x 1024(V) |
| Brightness Rating | 250 cd/m ² |
| Contrast Ratio | 1000:1 |
| Back Light | LED (30K) |
| Dot Pitch | 0.264(H) x 0.264(V)mm |
| Color Depth | 16.7M |
| Number of Pixels | 1,310,720 |
| Response Time | 5ms (Rising/Falling) |
| Audio Power / Speakers | 2 Speakers x 1.5 Watts |
| Viewing Angle (L/R/T/B) | 85/85/80/80 degrees |
| Digital Signal Processor | 3D Comb Filter |
| HDMI | x2 Inputs |
| Composite | x1 BNC Input; x1 Output |
| VGA | x1 VGA 15-pin D-sub Input |
| Audio | x1 L/R RCA Input; x1 3.5 PC stereo Input |
| Power | x1 2.1mm DC Input |
| Power Requirements | DC 12V (AC100~240)[50/60] |
| Power Consumption | 20 Watts (max) |
| Operating Temp | 32 ~ 104°F / 0 ~ 40°C |
| Humidity | 10% ~ 90% |
| Dimensions | 16.9" x 15.1" x 2.9" / 427.8 x 381.5 x 72mm |
| Cut-out Dimensions | 15.1 x 13.4 |
| Weight | Net: 11.4 lbs / 5.2 kg; Gross: 18.3 lbs / 8.3 kg |

Specifications subject to change.