



LED-1908HDL

This LED-backlit flush monitor features the latest technology with enhanced picture clarity and sharpness for both analog and digital video signals.

Benefits

- LED backlight: brighter picture using less power
- Displays 1080i/p digital video
- Analog video is very clear with no detail loss
- 3D Comb Filter for better picture quality
- Durable metal case

Related Products

- LED-1709HD: 17" standalone / wall-mount LCD Monitor
- LED-1709HDL: 17" flush-mount LCD Monitor
- LED-1709HDR: 17" rack-mount LCD Monitor
- LED-1908HD: 19" standalone / wall-mount LCD Monitor
- LED-1908HDR: 19" rack-mount LCD Monitor
- LED-1910HDVB: 19" standalone / wall-mount LCD High Brightness Monitor

Specifications	
Mount	VESA 100 x 100mm; Removable Deskstand
HD Compatible	Yes
Anti-Glare Coating	Yes
Case	Durable Metal
Native Aspect Ratio	5:4, displays 16:9; True 4:3 option available
Visible Screen Size	14.8" x 11.8" / 376.3 x 301mm
Resolution	1280(H) x 1024(V)
Brightness Rating	250 cd/m ²
Contrast Ratio	1,000:1
Back Light	LED (30K)
Dot Pitch	0.294(H) x 0.294(V)mm
Color Depth	16.7M
Number of Pixels	1,310,720
Response Time	9ms (Rising/Falling)
Audio Power/Speakers	x2 1.5 Watts
Viewing Angle	85/85/80/80 degrees
Digital Signal Processor	3D Comb Filter
HDMI	x2 Inputs
Composite	x1 BNC Input / x1 Output
VGA	x1 15-pin D-sub input
Audio	x1 RCA L/R Input; x1 PC stereo Input
Operating Temperature	32 ~ 104°F / 0 ~ 40°C
Humidity	10% to 90%
Power	x1 2.1mm DC Input
Power Requirements	DC 12V (AC100~240)[50/60]
Power Consumption	25 Watts (Max)
Dimensions	18.4" x 16.1" x 2.9" / 465.5 x 409 x 72mm
Cut-out Dimensions	16.5" x 14.6"
Weight	Net: 11.8 lbs / 5.4 kg; Gross: 17.3 lbs / 7.9 kg

Specifications subject to change.