



LED-2155HD

Commercial-grade, LED-backlit, LCD monitor displays Full HD without downscaling. This all-purpose model is designed for use in 24/7 environments and it is ideal for all video and computing applications.

Benefits
LED backlight: brighter picture using less power
Displays Full HD signals (1920 x 1080) with no downscaling
3D Comb Filter displays clearer image
Widescreen (16:9) native aspect ratio
Built-in removable deskstand
Built-in speakers

Accessories

WM-32: Wall-mount Bracket
WM-302: 4-way VESA wall mount with swing arm

Specifications	
Mount	VESA 100 x 100mm; Removable Deskstand
Case	Durable ABS Plastic
HD Compatible	Displays 1080i/p
Native Aspect Ratio	16:9
Visible Screen Size (WH)	18.03" x 10.14" / 457.92 x 257.58mm
Resolution	1920 x 1080 (Full HD)
Brightness Rating	250 cd/m² (Nit)
Contrast Ratio	1000:1
Back Light	LED
Dot Pitch	0.248 x 0.248mm
Color Depth	16.7 million
Number of Pixels	2,073,600
Response Time	5ms (Rising/Falling)
Audio Power / Speakers	x2 Speakers at 5 Watts
Viewing Angle (L/R/T/B)	85/85/85 degrees
Digital Signal Processing	3D Comb Filter
Operating Temp	32 ~ 104°F / 0 ~ 40°C
Humidity	10% ~ 95%
Power Requirements	100 ~ 240 V; 50/60 Hz
Power Consumption	< 25 Watt (Active); < 0.5 Watt (Stand-by)
VGA	x1 Input
HDMI	x1 Input
Composite	x1 BNC Input; x1 BNC Output
Audio	x1 3.5mm Input
Power	120 Volts
Dimensions w/ Deskstand	19.4" x 14.4" x 6.4" / 491.6 x 365.4 x 163.7mm
Dimensions	19.4" x 11.9" x 2.1" / 491.6 x 301.1 x 53.5mm
Weight	Net: 8.38 lbs / 3.8 kg

Product specifications subject to change.