



LED-3212HDT

Aesthetically-designed, commercial-grade, LED-backlit LCD monitor with ATSC / Clear QAM tuner provides exceptional picture quality using the latest DSP technology. This monitor is ideal for use in any commercial AV application.

Benefits

HD display (1080i/p) with high contrast ratio and 3D comb filter digital signal processing for better picture definition

LED backlight provides a brighter picture with a longer life using less power
Wide viewing angle

Accessories

WM-3270AR: 4-way wall mount that tilts -5 to +15 degrees with VESA pattern that supports up to 600 x 400mm. For 32" - 70" monitor; supports up to 90lbs

WM-3742: Fixed wall mount bracket - 200x200 to 600x400 VESA pattern

Specifications

Mount	VESA 100 x 200mm; Removable Deskstand
Anti Glare Coating	Yes
Case	Durable ABS Plastic
IR Remote Control	Yes
Native Aspect Ratio	16:9
Visible Screen Size (WH)	27.6" x 15.5" / 702 x 394mm
Native Resolution	1366(H) x 768(V) (displays 1080i/p)
Brightness Rating	280 cd/m ²
Contrast Ratio	1200:1
Digital Signal Processor	3D Comb Filter
Back Light	LED (30K)
Color Depth	16.7 million
Number of Pixels	2,073,600
Response Time	8ms (Rising/Falling)
Viewing Angle (L/R/T/B)	88/88/88/88 degrees
ATSC/QAM Tuner	x1 Digital ATSC/QAM; x1 F Connector Input
Component	x3 RCA YPbPr Inputs
Composite	x2 RCA Inputs; x1 RCA Output
HDMI	x3 Inputs
VGA	x1 RGB 15-pin D-sub Input
Audio	x2 3.5mm Input; x1 RCA L/R Output; x1 3.5mm earphone Input
Audio Power	2 Speakers x 8 Watts
USB	x1 Input for firmware updates only
Operating Temp	41 ~ 104°F / 5 ~ 40°C
Humidity	10% ~ 85%
Power	x1 AC Input
Power Requirements	100 ~ 240 VAC; 50/60 Hz
Power Consumption	55 Watts (Max); .5 Watts (Stand-by)
Dimensions	29.1" x 19.4" x 2.7" / 739 x 492 x 68mm
Weight	Net: 15.4 lbs / 7 kg; Gross: 19.8 lbs / 9 kg

Specifications subject to change.