



## LED-803HD

This adaptable small screen LED backlit monitor is ideal for use in security surveillance and professional AV environments where space can be limited and continuous use is often required.

### Benefits

- LED backlight: brighter picture using less power
- Anti-glare coating provides enhanced display
- Always-on capability when power is applied
- Multiple source connections
- Built-in speakers
- Durable metal case
- Remote control for easy access

### Accessories

- DC-1500: Factory approved car cord
- HM-401: Under-cabinet hinge mount (end of life)
- WM-32: Wall mount bracket (fixed/tilting)
- WM-302: Wall mount with 4-way adjustable swing arm

### Related Products

- LED-803HD2: Two 8" rack-mount, LED backlit, LCD monitors

Specifications	
Mount	Free-standing; ¼ - 20 pad top/bottom; VESA 75x75mm
HD Compatible	Yes
Anti-Glare Coating	Yes
Case	Metal
IR Remote Control	Yes
Native Aspect Ratio	4:3
Visible Screen Size	6.4" x 4.8" / 162 x 121.5mm
Resolution	800(H) x 600(V); displays up to 1080p
Brightness Rating	250 cd/m <sup>2</sup> (Nit)
Contrast Ratio	500:1
Back Light	LED (20K)
PC Compatibility	Yes
Dot Pitch	0.0675(H) x 0.2025(V) mm
Color Depth	16.7M
Number of Pixels	480,000
Response Time	25ms (Rising/Falling)
Audio Power/Speakers	x2 1.5 Watts
Viewing Angle	70/70/50/70 degrees
HDMI	x2 Inputs
Composite	x1 BNC Input / Output
PC	x1 15-pin D-sub Input
RS-232	x1 3.5mm Input
Audio	x2 RCA Inputs; x1 3.5mm PC Input
Power	x2 2.1mm DC Inputs
Power Requirements	11.5~13 VDC, 1.2A
Power Consumption	10 Watts (Max)
Operating Temperature	32 ~ 122°F / -20 ~ 80°C
Humidity	10% ~ 90% RH (Max)
Dimensions	8.8" x 6.9" x 1.9" / 223 x 176.2 x 47mm
Weight	Net: 2.9 lbs / 1.3 kg

Specifications subject to change.