



LED-3225-4K

32" LED-backlit LCD monitor has impressive picture quality with native Ultra HD resolution (3840 x 2160) commonly referred to as 4K resolution. This latest generation model is ideal for many uses including viewing multiple 4K and HD security cameras in 24/7 mission-critical environments. Ideal for use in perimeter security monitoring areas, smaller security operation centers, high volume retail locations, and in casino surveillance hubs.

Benefits

- Displays native Ultra HD (UHD) signals (3840x2160) with no downscaling
- LED backlight: brighter picture using less power
- Widescreen (16:9) native aspect ratio
- Multiple connections including HDMI, Composite and VGA
- Built-in removable desk stand
- Built-in speakers

Specifications	
Mount	VESA 200 x 100mm; Removable Deskstand
Anti Glare Coating	Yes
Case	Durable ABS Plastic
IR Remote Control	Yes
Native Aspect Ratio	16:9
Visible Screen Size (WH)	27.6" x 15.5" / 702 x 394mm
Resolution	3840(H) x 2160(V)
Brightness Rating	300 cd/m ² (Nit)
Contrast Ratio	3000:1
Back Light	LED (15K)
PC Compatibility	Yes
Dot Pitch	0.181(H) x 0.181(V) mm
Color Depth	1.07 Billion Colors
Number of Pixels	2,073,600
Response Time	8ms (Rising/Falling)
Audio Power / Speakers	8 Ohm, 2 Speakers x 5 Watts
Viewing Angle (L/R/T/B)	89/89/89/89 degrees
Digital Signal Processor	3D Comb Filter
HDMI Inputs	x1 HDMI 2.0, x2 HDMI 1.4
DisplayPort Input	x1 DP 1.4 (3840 x 2160 @ 60Hz)
VGA Input	x1 (1920 x 1080 @ 60Hz) 15-pin mini D-sub
Audio	x1 3.5mm Input; x1 3.5mm Output
Speakers	2 x 5 watts
Power	AC 100-240V 50/60HZ, Ext Power Supply
Power Consumption	50 Watts (Max)
Operating Temp	32 ~ 104°F / 0 ~ 40°C, Storage: (14° ~ 140°F) / -10° ~ 60°C
Humidity	10% ~ 90%
Dimensions w/ Deskstand W x H x D	29.25" x 19.8" x 7.1"; 743 x 503 x 180mm
Dimensions	29.25" x 19.8" x 2.2" / 362 x 267 x 55mm
Weight	Net: 15.4 lbs / 7 kgs

Specifications subject to change.